



CM-5-70
CM-5-100
CM-5-125
CM-5-150
CM-5-190
CM-5-240
CM-5-290

CM-6-70
CM-6-100
CM-6-125
CM-6-150
CM-6-190
CM-6-240
CM-6-290

CM-8-70
CM-8-100
CM-8-125
CM-8-150
CM-8-190
CM-8-240
CM-8-290



total plastificado blanco o negro sin incremento de precio
black or white total plasticized decor, no increase of price

MULTIDECK DISPLAY • VITRINAS MURALES

mod.	largo length (mm)	exposición display (m ²) CM-5	exposición display (m ²) CM-6	exposición display (m ²) CM-8	estantes shelves (uds) CM-5-6-8	potencia frig. frig. power (W) CM-5-6-8	consumo. consumption (W) CM-5-6-8	refrigerante refrigerant	rango range (°C)
CM-70	680	0,78	0,83	0,86	4	1315	1559	R-452A	-1 +5
CM-100	970	1,14	1,22	1,26	4	1497	1797	R-452A	-1 +5
CM-125	1220	1,45	1,56	1,6	4	1497	1800	R-452A	-1 +5
CM-150	1480	1,78	1,91	1,96	4	2963	2667	R-452A	-1 +5
CM-190	1880	2,28	2,45	2,52	8	2963	2698	R-452A	-1 +5
CM-240	2380	2,9	3,12	3,21	8	2994	3600	R-452A	-1 +5
CM-290	2900	3,56	3,82	3,92	8	5906	5333	R-452A	-1 +5

características técnicas y constructivas sujetas a variación sin previo aviso

we reserve the right to change specifications without prior notice

Vitrinas polivalentes, preparadas para carnes, lácteos y verduras regulando parámetros de la centralita digital

- Exterior en chapa de acero plastificado, interior en chapa de acero con acabado epoxi
- Costados de 30 mm con **doble cristal templado**
- Decoración estándar: costados gris y frontal a un color
- Perfilería en aluminio anodizado
- Paragolpes en la parte delantera
- Estantes regulables en altura y ángulo (100 Kg/m²), con porta-precios
- **De serie:** luz superior y cortina nocturna
- Iluminación LED 6500 K, opción LED 3000 K (luz cálida) o ROSA, al mismo precio
- Aislamiento de poliuretano inyectado, densidad 40 Kg/m³, cero efectos ODP y GWP
- Evaporador ventilado, con tratamiento EPOXY anti-corrosión de serie
- Descarche automático con evaporación automática
- Condensación ventilada
- Control electrónico de temperatura
- Indicador de temperatura
- Clase climática 3 (25°C 60%) régimen M1

M1 temperatura producto -1/+5°C UNE-EN ISO 23953-2:2006

All multideck are versatile and changing digital control parameters, are ready for meat, milk products and vegetables

- Laminated steel plate exterior, epoxy finished steel plate interior
- 30 mm thicknes sides with **tempered double glazed**
- Standard finishing: gray sides and one color front decor
- Anodised aluminium profiles
- Front rubber bumper
- Height and angle adjustable shelves (100 Kg/m²), with labels holder
- **Standard:** horizontal top lighting and night curtain
- 6500 K LED lighting, optional 3000 K LED (soft light) or PINK, same price
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Ventilated evaporator, with EPOXY anticorrosion cover as standard
- Auto defrost and automatic evaporation
- Ventilated condensation
- Electronic temperature controller
- External thermometer
- Climate class 3 (25°C 60%) regime M1

M1 product temperature -1/+5°C UNE-EN ISO 23953-2:2006

OPCIONES OPTIONS	decoración frontal front decor	decoración total total decor	lacado alto brillo glossy lacquered	interior lacado lacquered interior	Puertas Cristal doble templado Tempered double glazed doors	luz extra LED extra lighting	pre-instalación remote condenser unit
---------------------	-----------------------------------	---------------------------------	--	---------------------------------------	--	---------------------------------	--

CM-70
CM-100
CM-125
CM-150
CM-190
CM-240
CM-290

Versión REMOTO, incluye válvula de expansión (404A) y valvula solenoide
REMOTE version, expansion valve (404A) and solenoid valve, included

220v 60Hz / 115v 60Hz consultar - consult

all photos must be considered as a reference - fotografías no contractuales



CM-5-15

Eficiencia energética - Energy efficiency



Puertas cristal opcionales
Optional glass doors



CM-8-240