



CMb-5-50



CM-62

mod.	largo length (mm)	alto height (mm)	fondo depth (mm)	estantes shelves	capacidad capacity (L)	voltaje voltage	refrigerante refrigerant	potencia frig. frig. power W	potencia power W
CM-62	620	1870	640	4	375	230V-50Hz	R290	851	1430
CMb-5-50	530	1430	635	3	197	230V-50Hz	R290	851	1419

Características técnicas y constructivas sujetas a variación sin previo aviso.

We reserve the right to change specifications without prior notice.

- **CM-62**
- Exterior e interior en acero plastificado blanco
- **CMb-5-50**
- Exterior en acero plastificado blanco, costados exteriores en madera MDF, interior acero plastificado blanco
- Diseñados para bebidas y productos envasados
- Estantes de acero plastificado regulables en altura y ángulo, con porta-precios
- De serie: Luz horizontal, vertical y cortina nocturna
- Control digital de temperatura y descarches
- De serie: Luz vertical led y cortina nocturna
- Evaporación y condensación ventilada
- Aislamiento de poliuretano inyectado, libre CFCs, densidad 40 Kg/m³
- Evaporación automática del agua de descarche
- Clase climática 3 (25°C 60%HR) régimen M1, temperatura producto -1/5°C UNE EN ISO 23953-2:2006
- Tensión monofásica 230V 50Hz

- **CM-62**
- *Exterior and interior in white plastic coated steel*
- **CMb-5-50**
- *Exterior in white plastic coated steel, sides in MDF wood, white plasticized steel interior*
- *Designed for beverages and packaged*
- *Plastic coated steel shelves adjustable in height and angle, with porta-precios*
- *Hermetic compressor higher starting torque*
- *Standard: horizontal, vertical and night light curtain*
- *Digital temperature control and defrost*
- *Standard: Led vertical lighting and night blind*
- *Ventilated evaporation and condensation*
- *Insulation: Polyurethane, CFC, density 40 Kg / m³*
- *Automatic evaporation of defrost water*
- *Climatic class 3 (25°C 60%HR) regime M1, product temperature -1/5°C UNE EN ISO 23953-2:2006*
- *Voltage 230V 50Hz*

OPCIONES	OPTIONS
set 4 ruedas	4 castors set
230v 60Hz / 115v 60Hz	230v 60Hz / 115v 60Hz
otro color exterior	other external color

