

gama



mod.	rango range	largo length (mm)	alto height (mm)	fondo depth (mm)	consumo consumption (W)	capacidad capacity (L)	pares de guías sets of slides 60x80	tensión monofásica single phase voltage	refrigerante refrigerant
CP-78	-2°C+8°C	910	2100	1040	805	900	20	230V - 50 Hz	R-404A
CSG-80	-25°C-10°C	910	2100	1040	1060	900	20	230V - 50 Hz	R-404A

Características técnicas y constructivas sujetas a variación sin previo aviso.

We reserve the right to change specifications without prior notice.

all photos must be considered as a reference - fotografías no contractuales

Para a una correcta y controlada ventilación del producto, gracias a un sistema frigorífico infatigable, al servicio del usuario.

Cámara para refrigeración, con gran volumen interior (900 L.) con capacidad hasta 20 bandejas 600x800.

Ideal para conservar productos frescos, pastelería y panadería.

Diseñado para la conservación a temperatura negativa de una gran

Gracias a sus 900 L. de capacidad interior y a la uniforme distribución de la corriente de aire, permite conservar por muchas horas el producto sin pérdida de volumen.

For a corrected and controlled ventilation of the prod-uct and for an

indefatigable system at your service. Great capacity for the positive preservation, till 20 trays 600x800. Ideal to keep pastry and fresh prod-ucts.

CSG-80

Born for the negative conservation of large quantity of product. Thanks to its 900 liters of capacity and to a uni-form system of ventilation that keep also after several hours the air structure without losses of volume.

