


CVEA-9-10-TF
CVEA-9-13-TF
CVEA-9-15-TF
CVEA-9-20-TF
CVEA-9-25-TF
CVEA-9-30-TF



CVEE-9-10-TF
CVEE-9-13-TF
CVEE-9-15-TF
CVEE-9-20-TF
CVEE-9-25-TF
CVEE-9-30-TF

mod.	largo length (mm)	exposición display RSA (m ²)	reserva cold storage (m ³)	puertas doors (uds)	potencia frig. frig. power (W)	consumo consumption (W)	refrigerante refrigerant
CVEA-9-10	1055	0,65	0,33	1	522	419	R449A
CVEA-9-13	1305	0,82	0,43	2	635	1071	R449A
CVEA-9-15	1525	0,97	0,49	2	817	1107	R449A
CVEA-9-20	2025	1,31	0,67	3	1096	1377	R449A
CVEA-9-25	2525	1,65	0,84	4	1315	1433	R449A
CVEA-9-30	2995	1,96	1,19	4	1315	1472	R449A
CVEE-9-10	1055	0,65	0,33	1	522	419	R449A
CVEE-9-13	1305	0,82	0,43	2	635	1071	R449A
CVEE-9-15	1525	0,97	0,49	2	817	1107	R449A
CVEE-9-20	2025	1,31	0,67	3	1096	1377	R449A
CVEE-9-25	2525	1,65	0,84	4	1315	1433	R449A
CVEE-9-30	2995	1,96	1,19	4	1315	1472	R449A

- Exterior e interior en chapa de acero plastificada
- Plano exposición y encimera en acero inox AISI-304
- Bandejas plano de exposición lisas
- Costados de 40 mm en ABS inyectado excepto acabado madera
- **Decoración estándar:** costados cortos gris oscuro frontal gris + franja decorativa azul. Perfilera en aluminio anodizado
- Paragolpes en la parte delantera
- Cristal frontal auto-servicio
- **CVEE:** Iluminación LED 6500 K estándar: encimera superior y estante. Opción LED 3000 K (luz cálida) o ROSA, al mismo precio
- Aislamiento de poliuretano inyectado, densidad 40 Kg/m³, cero efectos ODP y GWP
- **Evaporador ventilado**, con tratamiento EPOXY anti-corrosión de serie
- Condensación ventilada, evaporación automática de serie (sólo con motor incorporado)
- Control electrónico de temperatura
- Indicador de temperatura
- Descarche automático
- Clase climática 3 (25°C 60%) régimen M1

M1 temperatura producto -1/+5°C UNE-EN ISO 23953-2:2006

- Interior and exterior finish in plastic coated steel
- Display area and counter in stainless steel AISI-304
- Smooth deck for display area
- 40 mm sides in injected ABS, except wood decor
- **Standard decoration:** short dark gray sides gray front+ blue decorative stripe
- Anodised aluminium profiles
- Front rubber bumper
- Self-service frontal glass
- **CVEE:** Standard LED 6500 K lighting: top worktop and shelf
- Optional 3000 K LED (soft light) or Fresh red, same price
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- **Ventilated evaporator**, with anticorrosion EPOXY treated as standard
- Ventilated condensation and automatic evaporation as standard (only models with condenser unit)
- Electronic temperature controller
- External thermometer
- Auto defrost
- Climate class 3 (25°C 60%) regime M1

M1 product temperature -1/+5°C UNE-EN ISO 23953-2:2006

SERVE OVER COUNTER • VITRINAS MODULARES

OPCIONES OPTIONS	decoración frontal front decor	decoración total total decor	lacado alto brillo High glossy lacquered	cierre plexi plexi doors	cierre cortina night blind	estante chasis chasis base	luz extra CVEE extra lighting	neutra neutral	pre-inst.
CV-10									
CV-13									
CV-15									
CV-20									
CV-25									
CV-30									

Versión REMOTO, incluye válvula de expansión (R449A) y valvula solenoide
REMOTE version, expansion valve (R449A) and solenoid valve, included

220v 60Hz / 115v 60Hz consultar - consult

Vitrina expositora modular serie 9 AUTOSERVICIO, con reserva
 Serve over counter modular line 9 SELF SERVICE, with cold storage

7

all photos must be considered as a reference - fotografías no contractuales



CVEA-9-20
 personalizada
 customized



CVEE-9-20
 lacado
 lacquered



opcional interior 440x270