



Disponible acabados de la carta NCS o RAL, incluidos en el precio estándar, excepto alto brillo y metalizados.

Available finish included in NCS or RAL color chart, at the same price, except glossy and metallic finishing

|               |
|---------------|
| VSS-6-6-RGB   |
| VSS-6-9-RGB   |
| VSS-6-13-RGB  |
| VSS-6-16-RGB  |
| VSSB-6-6-RGB  |
| VSSB-6-9-RGB  |
| VSSB-6-13-RGB |
| VSSB-6-16-RGB |

|               |
|---------------|
| VSS-6-6-RGM   |
| VSS-6-9-RGM   |
| VSS-6-13-RGM  |
| VSS-6-16-RGM  |
| VSSB-6-6-RGM  |
| VSSB-6-9-RGM  |
| VSSB-6-13-RGM |
| VSSB-6-16-RGM |

|              |
|--------------|
| VSS-6-6-RG   |
| VSS-6-9-RG   |
| VSS-6-13-RG  |
| VSS-6-16-RG  |
| VSSB-6-6-RG  |
| VSSB-6-9-RG  |
| VSSB-6-13-RG |
| VSSB-6-16-RG |

| mod.     | rango<br>range | largo<br>length<br>(mm) | fondo<br>depth<br>(mm) | alto<br>height<br>(mm) |      |      | exposición<br>display<br>TDA (m <sup>2</sup> ) |      |      | puertas<br>corredera<br>sliding<br>doors<br>(uds) | puertas<br>abatibles<br>hinged<br>doors<br>(uds) | refrigerante<br>refrigerant | potencia frig.<br>frig. power<br>(W) | consumo<br>consumption<br>(W) |
|----------|----------------|-------------------------|------------------------|------------------------|------|------|--|------|------|---|--|-----------------------------|--------------------------------------|-------------------------------|
|          |                |                         |                        | RGB                    | RGM  | RG   | RGB  | RGM  | RG   |   |  |                             |                                      |                               |
| VSS-6-6  | +2°C+8°C       | 580                     | 710                    | 1100                   | 1195 | 1380 | 0,45   | 0,5  | 0,54 | 0   | 1  | R449A                       | 817                                  | 1067                          |
|          |                |                         |                        |                        |      |      |  |      |      |   |  | R290*                       | 484                                  | 879                           |
| VSS-6-9  | +2°C+8°C       | 930                     | 710                    | 1100                   | 1195 | 1380 | 0,77   | 0,85 | 0,9  | 2   | 0  | R449A                       | 1096                                 | 1376                          |
|          |                |                         |                        |                        |      |      |  |      |      |   |  | R290*                       | 988                                  | 1174                          |
| VSS-6-13 | +2°C+8°C       | 1280                    | 710                    | 1100                   | 1195 | 1380 | 1,08   | 1,2  | 1,26 | 2   | 0  | R449A                       | 1096                                 | 1739                          |
|          |                |                         |                        |                        |      |      |  |      |      |   |  | R290*                       | 988                                  | 1537                          |
| VSS-6-16 | +2°C+8°C       | 1630                    | 710                    | 1100                   | 1195 | 1380 | 1,4  | 1,55 | 1,62 | 2   | 0  | R449A                       | 1497                                 | 1963                          |
|          |                |                         |                        |                        |      |      |  |      |      |   |  | R290*                       | 1602                                 | 1863                          |

\*opcional - optional

Características técnicas y constructivas sujetas a variación sin previo aviso

**VSS**-vitrina refrigerada para snack (+2°+8°)

**VSSB**-vitrina refrigerada para chocolates (+14°+17°, 55% HR)

- Exterior fabricado en chapa de acero plastificada, lacada o inox
- Costados en cristal doble templado, máxima visibilidad
- Interior en acero inoxidable AISI-304 18/10.
- **Cristal doble templado:** costados, frente, encimera y puertas
- Perfilera en aluminio anodizado
- Estantes y encimera de cristal, con iluminación LED 6500 K
- Opción LED 3000 K (luz cálida) o ROSA, al mismo precio
- Aislamiento de poliuretano inyectado, densidad 40 Kg/m<sup>3</sup>, cero efectos ODP y GWP
- Evaporador ventilado
- Descarche automático con evaporación automática
- Condensación ventilada
- Control electrónico de temperatura
- Indicador de temperatura
- Clase climática 3 ( 25°C 60%) régimen M1

Todos los modelos se pueden personalizar en decoración  
Cualquier decoración incluida en el precio, excepto alto brillo y metalizados

We reserve the right to change specifications without prior notice

**VSS**- snacks refrigerated (+2°+8°)

**VSSB**- chocolate refrigerated (+14°+17°, 55% HR)

- External finish in plastic coated steel, lacquered or stainless steel
- Double glazed sides, max visibility
- Internal finish in AISI-304 18/10 stainless steel
- **Tempered double glazed:** sides, front, top and doors
- Anodised aluminium profiles
- Glass top and shelves, with 6500 K LED lighting
- Optional 3000 K LED (soft light) or PINK, same price
- 40 Kg/m<sup>3</sup> density polyurethane insulation, zero ODP and GWP
- Ventilated evaporator
- Auto defrost and automatic evaporation
- Ventilated condensation
- Electronic temperature controller
- External thermometer
- Climate class 3 ( 25°C 60%) regime M1

All models can be customized in decoration  
All decorations are included on price, except glossy or metallic finishing

|                       |                           |
|-----------------------|---------------------------|
| 230v 60Hz / 115v 60Hz | consultar - consult       |
| R290                  | mismo precio - same price |



VSS  
+2°C+8°C



all photos must be considered as a reference - fotografías no contractuales



VSS-6-9-RG



VSS-6-9-RGM



VSS-6-9-RGB

