



CM-6-70-LE  
 CM-6-100-LE  
 CM-6-125-LE  
 CM-6-150-LE  
 CM-6-190-LE  
 CM-6-240-LE  
 CM-6-290-LE

CMI-6-70-LE  
 CMI-6-100-LE  
 CMI-6-125-LE  
 CMI-6-150-LE  
 CMI-6-190-LE  
 CMI-6-240-LE  
 CMI-6-290-LE



mod.	largo length (mm)	exposición display TDA (m <sup>2</sup> )	estantes shelves (uds)	potencia frig. frig. power (W)	consumo. consumption (W)	refrigerante refrigerant	rango range (°C)
CM-70	680	0,83	4	1315	1661	R449A	-1 +5
CM-100	970	1,22	4	1497	1949	R449A	-1 +5
CM-125	1220	1,56	4	1497	1952	R449A	-1 +5
CM-150	1480	1,91	4	2953	3076	R449A	-1 +5
CM-190	1880	2,45	8	2953	3108	R449A	-1 +5
CM-240	2380	3,12	8	2994	3924	R449A	-1 +5
CM-290	2900	3,82	8	5906	6175	R449A	-1 +5

MULTIDECK DISPLAY • VITRINAS MURALES

características técnicas y constructivas sujetas a variación sin previo aviso

Vitrinas polivalentes, preparadas para carnes, lácteos y verduras regulando parámetros de la centralita digital

- **CM-LE:** Paneles frontales decorables e interior en chapa de acero con acabado epoxi
  - **CMI-LE:** Paneles frontales e interior en acero inox AISI-304
  - **Costados de cristal doble templado**
  - **De serie:** luz superior y cortina nocturna
  - Iluminación LED 6500 K, opción LED 3000 K (luz cálida) o ROSA, al mismo precio
  - Perfilera en aluminio anodizado
  - Paragolpes en la parte delantera
  - Estantes regulables en altura y ángulo (100 Kg/m<sup>2</sup>), con porta-precios
  - Aislamiento de poliuretano inyectado, densidad 40 Kg/m<sup>3</sup>, cero efectos ODP y GWP
  - Evaporador ventilado, con tratamiento EPOXY anti-corrosión de serie
  - Descarche automático con evaporación automática
  - Condensación ventilada
  - Control electrónico de temperatura
  - Indicador de temperatura
  - Clase climática 3 ( 25°C 60%) régimen M1
- M1 temperatura producto -1/+5°C UNE-EN ISO 23953-2:2006

we reserve the right to change specifications whitout prior notice

All multideck are versatile and changing digital control parameters, are ready for meat, milk products and vegetables

- **CM-LE:** Decorable frontal panels, epoxy finished steel plate interior
  - **CMI-LE:** AISI-304 stainless Steel frontal panels and interior
  - **Double glazed tempered sides**
  - **Standard:** horizontal top lighting and night curtain
  - 6500 K LED lighting, optional 3000 K LED (soft light) or PINK, same price
  - Anodised aluminium profiles
  - Front rubber bumper
  - Height and angle adjustable shelves (100 Kg/m<sup>2</sup>), with labels holder
  - 40 Kg/m<sup>3</sup> density polyurethane insulation, zero ODP and GWP
  - Ventilated evaporator, with EPOXY anticorrosion cover as standard
  - Auto defrost and automatic evaporation
  - Ventilated condensation
  - Electronic temperature controller
  - External thermometer
  - Climate class 3 ( 25°C 60%) regime M1
- M1 product temperature -1/+5°C UNE-EN ISO 23953-2:2006

OPCIONES OPTIONS	decoración frontal front decor	luz extra LED x estante extra lighting x shelf	pre-instalación remote condenser unit
CM-70			
CM-100			
CM-125			
CM-150			
CM-190			
CM-240			
CM-290			

Versión REMOTO, incluye válvula de expansión (R449A) y válvula solenoide  
 REMOTE version, expansion valve (R449A) and solenoid valve, included

220v 60Hz / 115v 60Hz consultar - consult

Vitrina expositora MURAL COSTADOS PANORÁMICOS  
MULTIDECK PANORAMIC SIDES display

8



all photos must be considered as a reference - fotografías no contractuales



CM-6-190-LE

VITRINAS  
MURALES  
8