



eficiente ahorro energético
efficient energy saving



total exterior plastificado blanco o negro sin incremento de precio
external black or white total plasticized decor, no increase of price

CM-5-100-EG
CM-5-125-EG
CM-5-150-EG
CM-5-190-EG
CM-5-240-EG
CM-5-290-EG

CM-6-100-EG
CM-6-125-EG
CM-6-150-EG
CM-6-190-EG
CM-6-240-EG
CM-6-290-EG

CM-8-100-EG
CM-8-125-EG
CM-8-150-EG
CM-8-190-EG
CM-8-240-EG
CM-8-290-EG

mod.	largo length (mm)	puertas doors (uds)	exposición display TDA (m ²) CM-5-EG	exposición display TDA (m ²) CM-6-EG	exposición display TDA (m ²) CM-8-EG	estantes shelves (uds) CM-5-6-8-EG	potencia frig. frig. power (W) CM-5-6-8-EG	consumo. consumption (W) CM-5-6-8-EG	refrigerante refrigerant	rango range (°C)
CM-100-EG	970	2	0,96	0,99	1,02	4	1315	1671	R449A	-1 +5
CM-125-EG	1220	2	1,22	1,26	1,29	4	1315	1674	R449A	-1 +5
CM-150-EG	1480	3	1,5	1,54	1,57	4	1755	1966	R449A	-1 +5
CM-190-EG	1880	4	1,92	1,98	2,01	8	1755	2041	R449A	-1 +5
CM-240-EG	2380	4	2,44	2,52	2,55	8	2953	2821	R449A	-1 +5
CM-290-EG	2900	6	2,99	3,09	3,12	8	3515	3931	R449A	-1 +5

características técnicas y constructivas sujetas a variación sin previo aviso

we reserve the right to change specifications without prior notice

Vitrinas polivalentes, preparadas para carnes, lácteos y verduras regulando parámetros de la centralita digital

- Exterior en chapa de acero plastificado, interior en chapa de acero con acabado epoxi
 - Costados de 30 mm con **doble cristal templado**
 - **Decoración estándar:** costados gris y frontal a un color
 - Perfilería en aluminio anodizado
 - Paragolpes en la parte delantera
 - Estantes regulables en altura y ángulo (100 Kg/m²), con porta-precios
 - **De serie:** luz superior y **puertas doble cristal templado**
 - Iluminación LED 6500 K, opción LED 3000 K (luz cálida) o ROSA, al mismo precio
 - Aislamiento de poliuretano inyectado, densidad 40 Kg/m³, cero efectos ODP y GWP
 - Evaporador ventilado, con tratamiento EPOXY anti-corrosión de serie
 - Descarche automático con evaporación automática
 - Condensación ventilada
 - Control electrónico de temperatura
 - Indicador de temperatura
 - Clase climática 3 (25°C 60%) régimen M1
- M1 temperatura producto -1/+5°C UNE-EN ISO 23953-2:2006

All multideck are versatile and changing digital control parameters, are ready for meat, milk products and vegetables

- Laminated steel plate exterior, epoxy finished steel plate interior
 - 30 mm thickness sides with **tempered double glazed**
 - **Standard finishing:** gray sides and one color front decor
 - Anodised aluminium profiles
 - Front rubber bumper
 - Height and angle adjustable shelves (100 Kg/m²), with labels holder
 - **Standard:** horizontal top lighting and **double tempered glazed doors**
 - 6500 K LED lighting, optional 3000 K LED (soft light) or PINK, same price
 - 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
 - Ventilated evaporator, with EPOXY anticorrosion cover as standard
 - Auto defrost and automatic evaporation
 - Ventilated condensation
 - Electronic temperature controller
 - External thermometer
 - Climate class 3 (25°C 60%) regime M1
- M1 product temperature -1/+5°C UNE-EN ISO 23953-2:2006

decoración frontal front decor	decoración total total decor	lacado alto brillo glossy lacquered	interior negro black interior	luz extra LED x estante extra lighting x shelf	pre-instalación remote condenser unit
OPCIONES OPTIONS					

- CM-70
- CM-100
- CM-125
- CM-150
- CM-190
- CM-240
- CM-290

Versión REMOTO, incluye válvula de expansión (R449A) y válvula solenoide
REMOTE version, expansion valve (R449A) and solenoid valve, included

220v 60Hz / 115v 60Hz consultar - consult

Vitrina expositora MURAL serie 5 - 6 - 8 CON PUERTAS
5 - 6 - 8 series MULTIDECK WITH DOORS display

8

all photos must be considered as a reference - fotografías no contractuales



luz estante opcional
optional shelf lighting



CM-5-125-EG



CM-6-190-EG