


- CM-6-70-V
- CM-6-100-V
- CM-6-125-V
- CM-6-150-V
- CM-6-190-V
- CM-6-240-V
- CM-6-290-V

- CM-8-70-V
- CM-8-100-V
- CM-8-125-V
- CM-8-150-V
- CM-8-190-V
- CM-8-240-V
- CM-8-290-V



exterior total plastificado blanco o negro sin incremento de precio
 exterior black or white total plastified decor, no increase of price

mod.	largo length (mm)	exposición display TDA (m ²)	exposición display TDA (m ²)	estantes shelves (uds)	potencia frig. frig. power (W)	consumo. consumption (W)	refrigerante refrigerant	rango range (°C)
		CM-6	CM-8	CM-6-8	CM-6-8	CM-6-8	CM-6-8	
CMV-70	680	0,83	0,86	3	1315	1559	R449A	+1 +10
CMV-100	970	1,22	1,26	3	1497	1797	R449A	+1 +10
CMV-125	1220	1,56	1,6	3	1497	1800	R449A	+1 +10
CMV-150	1480	1,91	1,96	3	2963	2667	R449A	+1 +10
CMV-190	1880	2,45	2,52	6	2963	2698	R449A	+1 +10
CMV-240	2380	3,12	3,21	6	2994	3600	R449A	+1 +10
CMV-290	2900	3,82	3,92	6	5906	5333	R449A	+1 +10

características técnicas y constructivas sujetas a variación sin previo aviso

we reserve the right to change specifications without prior notice

MULTIDECK DISPLAY • VITRINAS MURALES

- Vitrinas, preparadas frutas y verduras
- Exterior en chapa de acero plastificado, interior en chapa de acero con acabado epoxy
 - Costados de 30 mm con **double cristal templado**
 - **Decoración estándar:** costados gris y frontal a un color
 - Perfilaría en aluminio anodizado
 - Paragolpes en la parte delantera
 - Estantes regulables en altura (100 Kg/m²), inclinados, con porta-precios y barandilla en la parte delantera
 - Espejo en la parte superior
 - **De serie:** luz superior y cortina nocturna
 - Iluminación LED 6500 K, opción LED 3000 K (luz cálida) o ROSA, al mismo precio
 - Aislamiento de poliuretano inyectado, densidad 40 Kg/m³, cero efectos ODP y GWP
 - Evaporador ventilado, con tratamiento EPOXY anti-corrosión de serie
 - Descarche automático con evaporación automática
 - Condensación ventilada
 - Control electrónico de temperatura
 - Indicador de temperatura
 - Clase climática 3 (25°C 60%) régimen M1
- M1 temperatura producto -1/+5°C UNE-EN ISO 23953-2:2006

- Multideck ready for fruits and vegetables
- Laminated steel plate exterior, epoxy finished steel plate interior
 - 30 mm thicknes sides with **tempered double glazed**
 - Standard finishing: gray sides and one color front decor
 - Anodised aluminium profiles
 - Front rubber bumper
 - Height adjustable shelves (100 Kg/m²), with labels holder, and front railing
 - Mirror on top
 - **Standard:** horizontal top lighting and night curtain
 - 6500 K LED lighting, optional 3000 K LED (soft light) or PINK, same price
 - 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
 - Ventilated evaporator, with EPOXY anticorrosion cover as sta dard
 - Auto defrost and automatic evaporation
 - Ventilated condensation
 - Electronic temperature controller
 - External thermometer
 - Climate class 3 (25°C 60%) regime M1
- M1 product temperature -1/+5°C UNE-EN ISO 23953-2:2006

OPCIONES OPTIONS	decoración frontal front decor	decoración total total decor	lacado alto brillo glossy lacquered	interior negro black interior	luz extra LED x estante extra lighting x shelf	pre-instalación remote condenser unit
---------------------	--------------------------------	------------------------------	-------------------------------------	----------------------------------	---------------------------------------------------	------------------------------------------

- CM-70
- CM-100
- CM-125
- CM-150
- CM-190
- CM-240
- CM-290

Versión REMOTO, incluye válvula de expansión (R449A) y válvula solenoide
 REMOTE version, expansion valve (R449A) and solenoid valve, included

220v 60Hz / 115v 60Hz consultar - consult

Vitrina expositora frutas y verduras MURAL serie 6 - 8
6 - 8 series MULTIDECK fruit and vegetables display

8



all photos must be considered as a reference - fotografías no contractuales



CM-6-150-V

VITRINAS
MURALES
8