


 MRGP-120
 MCGP-120

 MRGP-170
 MCGP-170

 MRGP-220
 MCGP-220


MRGP-270


 MRGPV-120
 MCGPV-120

 MRGPV-170
 MCGPV-170

 MRGPV-220
 MCGPV-220


MRGPV-270

mod.	rango range °C	largo length (mm)	alto height (mm)	fondo depth (mm)	estantes shelves GN 1/1	pares guías slides sets	volumen capacity (L)	volumen neto net capacity (L) 2015/1094	voltaje voltage	potencia frig. frig. power	refrigerante recomendado recommended refrigerant
MRGP / MRGPV-120	-2°C +8°C	1045	850	700	2	2	255	187	230V-50Hz	300	R134a
MRGP / MRGPV-170	-2°C +8°C	1495	850	700	3	3	399	309	230V-50Hz	356	R134a
MRGP / MRGPV-220	-2°C +8°C	1945	850	700	4	4	543	430	230V-50Hz	485	R134a
MRGP / MRGPV-270	-2°C +8°C	2395	850	700	5	5	686	552	230V-50Hz	485	R134a
MCGP / MCGPV-120	-20°C -15°C	1045	850	700	2	2	255	187	230V-50Hz	353	R452A
MCGP / MCGPV-170	-20°C -15°C	1495	850	700	3	3	399	309	230V-50Hz	452	R452A
MCGP / MCGPV-220	-20°C -15°C	1945	850	700	4	4	543	430	230V-50Hz	610	R452A

Características técnicas y constructivas sujetas a variación sin previo aviso.

We reserve the right to change specifications without prior notice.

- **MRGP / MCGP:** Contrapuerta inox embutida
- **MRGPV / MCGPV:** doble cristal + LEDs

- **MRGP / MCGP:** inner side of doors by stamped steel
- **MRGPV / MCGPV:** double glazed doors + LEDs


- Exterior en acero inox AISI-304, excepto el respaldo
- Interior en acero inox AISI-304, con aristas curvas y fondo embutido
- Puertas de apertura reversible, con sistema de cierre automático y burlete magnético (permanece abierta al superar los 90° de apertura)
- Encimera de acero inox AISI-304 con frente curvo y peto trasero sanitario de 100 mm (opcional sin peto)
- Estantes interiores GN 1/1 de alambre en acero plastificado, regulables en altura
- Pies en tubo de acero inox ajustables en altura 135 - 210 mm
- Unidad condensadora **NO INCLUIDA**
- Control de expansión de refrigerante **NO INCLUIDO**
- Rendimiento del evaporador con $\Delta t=12^\circ\text{C}$
- Evaporador sistema tiro forzado, con recubrimiento epoxi anticorrosión
- Aislamiento de poliuretano inyectado, densidad 40 Kg/m³, cero efectos ODP y GWP
- Control digital de temperatura, descarches optimizados, alarma por alta temperatura de condensación (opcional). Eficiente gestión del consumo de energía
- Condiciones de trabajo: MRGP / MCGP 40°C ambiente
MRGPV / MCGPV 32°C ambiente

- AISI-304 stainless steel exterior, rear side galvanized panel
- AISI-304 stainless steel interior, stamped bottom and rounded corners
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- AISI-304 stainless steel worktop, with rounded front and 100 mm sanitary upstand (optional without upstand)
- GN 1/1 shelves made of plasticized steel wire, height adjustable
- AISI -304 adjustable legs, 135 to 210 mm
- Condenser unit **NOT INCLUDED**
- Refrigerant expansion control, **NOT INCLUDED**
- Performance of the evaporator with $Dt = 12^\circ\text{C}$
- Fan assisted evaporator, with epoxi anticorrosion coating.
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost, high-temperature condensation alarm (optional). Efficient management of energy consumption
- Operating: MRG / MCG 40°C ambient
MRGV / MCGV 32°C ambient

	Incremento precio por cambio de puerta a cajonera doble refrigerada inox desmontable sobre guías inox telescópicas, sistema auto-cierre (MRGP)	Increase of price by changing door to double drawers set, detachable telescopic SS runners, soft-closing system (MRGP)
	Incremento precio por cambio de puerta a cajonera triple refrigerada inox desmontable sobre guías inox telescópicas, sistema auto-cierre (MRGP)	Increase of price by changing door to triple drawers set, detachable telescopic SS runners, soft-closing system (MRGP)

OPCIONES

OPCIONES	OPTIONS
parrilla adicional GN 1/1	GN 1/1 extra shelf
parrilla suplemento	extra shelf supplement
set adicional guías GN 1/1	GN 1/1 slides extra set
conexiones lado izquierdo	left side connections
encimera sin peto	no upstand worktop
cerradura puerta inox	SS door lock
cerradura puerta cristal	glass door lock
registrador de alarmas HACCP	HACCP alarm recorder
230v 60Hz / 115v 60Hz	230v 60Hz / 115v 60Hz
respaldo inox	stainless steel rear side
evaporación automática	defrost water evaporadtion



Mesa fría GN 1/1, refrigeración y congelados PRE-INSTALACION
GN 1/1 chiller and freezer counter, for REMOTE condenser unit

1

all photos must be considered as a reference - fotografías no contractuales



MRGP-220



MRGPV-220

